



**NBS SPECIFICATION FOR
K-K CLASS 0
35MM CLASS ZERO INDOOR HOARDING PANEL - 01.10.16**

K30 Panel Partitions

TYPE OF HOARDING

112 RE-LOCATABLE HOARDING SYSTEM: CLASS 0 SURFACE SPREAD OF FLAME

- Hoarding type: Temporary
- Supplier: **Kwik-Klik Hoardings Limited**
10-14 Ward Street, Bradford, West Yorkshire, BD7 3PR
Telephone: 01274 525 660 Email: info@kwik-klik.co.uk
www.kwik-klik.co.uk
- Product reference: **Class 0**
- Panel Type: Extruded PVC Panel Partition
- Panel Thickness: 35mm
- Panel Widths: 500mm
- Panel Material Source: Recycled
- Colour: White
- Fixings: Consult with supplier, identifying hoarding height
- Partition height: As site requirements. 3000mm to 4500mm | bespoke on request
- Partition abutments:
 - Top: Top Trim 35mm
 - Bottom: Trim 35mm
 - Deflection allowance: To Structural Engineer's Recommendation.
 - Floor: 35mm Base Track Channel.
- Partition joints:
 - Vertical: Interlocking Panels
 - Horizontal: 35mm H-Divider (if needed)
 - 90 Degree Corners: 50mm Corner Flashing
 - Non-90 Degree Corners: 50mm x 50mm Flexi Angle
- Accessories: Flexi Angle at Window Reveals / Openings.

INSTALLATION

410 WORKMANSHIP GENERALLY

- Setting out: Plumb, true to line and level, and free from bowing, undulations and other planar distortions.
- Joints: Align accurately with no lipping.
- Stability: Fixes securely to horizontal scaffold bars at rear using special clips
- Moisture and thermal movement of framing/ panels: Make adequate allowance.

425 INSTALLING RE-LOCATABLE HOARDINGS

- Site dimensions: Check before installation. Give notice of discrepancies.
- Perimeter abutments: Accommodate deviations whilst maintaining partition system performance. Form make up/ closer pieces accurately around projections and features.

- Customisation: Do not cut or otherwise alter framing/ panels on site, except where shown on drawings.
- Intermediate joints in exposed frame members and trims: Keep to a minimum.