



**NBS SPECIFICATION FOR
FIRE RATED HALF HOUR (FR30)
100MM INDOOR HOARDING /PARTITION PANEL - 01.10.16**

K30 Panel Partitions – Metal Faced Insulated Hoarding Panel

TYPE OF HOARDING

112 RE-LOCATABLE HOARDING SYSTEM: FIRE-RATED HALF HOUR 1200

- Hoarding type: Temporary Partition
 - Supplier: **Kwik-Klik Hoardings Limited**
10-14 Ward Street, Bradford, West Yorkshire, BD7 3PR
Telephone: 01274 525 660 Email: info@kwik-klik.co.uk
www.kwik-klik.co.uk
 - Product reference: **Fire Rated Half Hour (FR30)**
 - Panel Type: Fire-Rated infill partition
 - Panel Thickness: 100mm
 - Panel Widths: 1200mm
 - Panel Material Source: various
 - Colour: White | Grey / Other colours available
 - Fixings: Consult with Manufacturer, identifying hoarding height
- Partition height: As site requirements
- Partition abutments:
 - Top: Top Channel 100mm
Bottom: Bottom Channel 100mm
Deflection allowance: To Structural Engineer's Recommendation.
 - Floor: 100mm Base Track Channel.
- Partition joints:
 - Vertical: Interlocking Panels
 - 90 Degree Ext Corners: 150mm x 50mm Ext Corner Flashing
 - 90 Degree Int Corners: 50mm x 50mm Int Corner Flashing
- Accessories: Flexi Angle at Window Reveals / Openings.

INSTALLATION

410 WORKMANSHIP GENERALLY

- Setting out: Plumb, true to line and level, and free from bowing, undulations and other planar distortions.
- Joints: Align accurately with no lipping.
- Stability: Fixes securely within top and bottom channels
- Moisture and thermal movement of framing/ panels: Make adequate allowance.

425 INSTALLING RE-LOCATABLE HOARDINGS

- Site dimensions: Check before installation. Give notice of discrepancies.
- Perimeter abutments: Accommodate deviations whilst maintaining partition system's half hour fire-rated performance. Form make up / close pieces accurately around projections

and features.

- Customisation: Do not cut or otherwise alter framing/ panels on site, except where shown on drawings.
- Intermediate joints in exposed frame members and trims: Keep to a minimum.